


SEE LENGTH TABLE



#### BILL OF MATERIALS

ITEM	QTY	SUPPLIER	SUPPLIER PN	DESCRIPTION	RACELOGIC P/N
1	1	APEM	IPR3SAD2	BLACK NON-LATCHING PUSH SWITCH	IPR3SAD2
2	1	RACELOGIC	VBSWITHANDLE	SWITCH HANDLE	VBSWITHANDLE
3	1	FARNELL	129-6997	SMALL CABLE TIE	129-6997
4	1	LEMO	GMA.0B.030.DN	BLACK LEMO BOOT	GMA.0B.030.D
5	3 x 10mm	FARNELL	100-8442	HEATSHRINK 3.2/1.6 BLACK	119-0793
6	A/R	CPC	CBBR6603	SECURITY ALARM CABLE 4 CORE BLACK	PP01557
7	30mm	FARNELL	304-6539	HEATSHRINK CLEAR 6mm 3:1	304-6539
8	1	AVERY	J8656-25	CABLE IDENT ON 25.4 x 10mm LABEL	-
9	5mm	FARNELL	119-1021	1.5mm 3:1 BLACK HEATSHRINK	119-1021
10	1	VISHAY	RN55C1002FB14	10k METAL FILM RESISTOR 1/8watt 1% 50ppm	RN55C1002FB14

#### NOTES:

- Don't fit boot (item 4) to handle until the switch has been fitted.
- Twist cable with switch (item 1) while threading in.
- Label to read from left to right from unterminated wires end.
- Reference the "Length Table" for the correct stock code marking.
- Solder wires to the contacts on switch (item 1) and insulate with heatshrink (item 5).
- Solder resistor to contact on the switch and to the yellow and black wires as shown in the diagram.
- Use Heatshrink (Item 9) over solder joint inside handle.

#### LENGTH TABLE

STOCK CODE	LENGTH
RLACS362	2.5m ± 20mm
RLACS362-5	5m ± 50mm

**RACELOGIC**

Unit 10 Swan Business Centre,  
Osier Way, Buckingham, MK18 1TB  
Email: hardware@racelogic.co.uk  
Tel: +44 (0)1280 823803

	NAME	DATE
DRAWN	D.KOZYRA	27/06/25
CHK'D	S.TAYLOR	27/06/25
APP'V'D	S.TAYLOR	27/06/25

DWG NUMBER : RLACS362-X

DESCRIPTION : HAND HELD TRIGGER

REDMINE NUMBER : 25410

REVISION: 3

IF YOU ARE UNSURE ABOUT SOMETHING OR WOULD LIKE TO DEVIATE FROM THE DRAWING TO EASE MANUFACTURE, PLEASE CONTACT THE DESIGNER (DRAWN)

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN MILLIMETRES

TOLERANCES: LINEAR: ±10mm  
ANGULAR: ±10°

DRAWING NOT TO SCALE

SHEET 1 OF 1

A4