


Length variable see length requirements table



WIRE ENTRY
FGG.0B.303.CLAD52Z

BILL OF MATERIALS

ITEM	QTY	SUPPLIER	PART NUMBER	DESCRIPTION	RACELOGIC PN
1	1	LEMO UK	FGG.0B.303.CLAD52Z	LEMO 3 WAY PLUG	LEMO 3WAY P
2	1	CAMBERTRONICS	GMA.0B.040.DN	LEMO BLACK SLEEVE	GMA.0B.040.D
3	A/R	RAPID	7-2-04A	4 CORE, UNSCREENED BLACK CABLE	119-0211
4	1	AVERY	J8658-25	25.4 x 10mm LABEL + CABLE IDENT	-
5	30mm	FARNELL	304-6539	HEATSHRINK CLEAR 6mm 3:1	304-6539
6	20mm	CPC	CB09683	4.8mm 2:1 HEATSHRINK BLACK	100-8431

CONNECTOR WIRING		
3 WAY P		
PIN	COLOUR	FUNCTION
1	RED	ANALOGUE OUTPUT
2	BLUE	DIGITAL OUTPUT
3	YELLOW	ANALOGUE GROUND
SHELL	GREEN	GROUND

LENGTH REQUIREMENTS		
CABLE NAME	LENGTH	TOLERANCE
RLCAB007	1m	+/-20mm
RLCAB007-2	2m	+/-20mm

DRAWING NUMBER	RLCAB007-X	DRAWN	H.HUSSAIN	SHEET	1/1
DESCRIPTION	3 WAY LEMO TO 4 WIRE UNTERMINATED				
REVISION					
ISS	DESCRIPTION	DATE	APPROVED	REDMINE	
8	CHANGED CABLE TYPE TO 4 CORE	06/07/23	SH	21563	