


WIRE ENTRY
FGG.0B.305.CLAD52Z

NOTES:

- Insulate solder joints with appropriate size heatshrink (119-1021)
- Place 2 x 10mm of black heatshrink 100-8431 under collect



WIRE ENTRY
FGA.0K.306.CLAC50Z

LENGTH TABLE			
CABLE	LENGTH	TOLERANCE	CABLE
RLCAB120	2m	+/-20mm	LCPRN062801
RLCAB120-3	3m	+/-20mm	LCPRN062801
RLCAB120-5	5m	+/-20mm	LCPRN062801
RLCAB120-10	10m	+/-20mm	LCPRN062801
RLCAB120-20	20m	+/-20mm	LCPRN062801

BILL OF MATERIALS					
ITEM	QTY	MANUFACTURER	MANUFACTURER P/N	DESCRIPTION	RACELOGIC P/N
1	1	LEMO	FGG.0B.305.CLAD52Z	LEMO 5 WAY PLUG	LEMO 5WAY P
2	2	LEMO	GMA.0B.035.DA	LEMO BLUE STRAIN BOOT	GMA.0B.035DA
3	A/R	GUANGZHOU	LCPRN062801	6 CORE + SCREEN CABLE BLACK	LCPRN062801
4	1	AVERY	J8658-25	25.4 X 10mm CABLE LABEL	-
5	30mm	PRO POWER	CGFC-6/2-X	HEATSHRINK 6mm 3:1 CLEAR	304-6539
6	A/R	PRO POWER	13636	HEATSHRINK 5mm 2:1	100-8431
7	1	LEMO	FGA.0K.306.CLAC50Z	LEMO 6 WAY PLUG SPLASHPROOF A KEY	LEMO 6W PS-A
8	A/R	MULTICOMP PRO	SP3X15/5/BLACK	HEATSHRINK 1.5mm 3:1 BLACK	119-1021

WIRING TABLE			
5 WAY P			6 WAY PS
PIN	FUNCTION	COLOUR	PIN
3	CAN H	ORANGE	3
4	CAN L	GREEN	4
5	POWER	RED	5
		YELLOW	
SHELL	GND	BLACK	SHELL
		BROWN	

DRAWING NUMBER	RLCAB120-x	DRAWN	B.SELBY	SHEET	1/1
DESCRIPTION	6W S/P LEMO PLG TO 5W LEMO PLUG 2m				
REVISION					
ISS	DESCRIPTION	DATE	APPROVED	REDMINE	
5	DOUBLING UP OF POWER WIRES	24-07-20	SH	15667	