


WIRE ENTRY  
FGG.0B.304.CLAD52Z

NOTES:  
-Fit item 8 under connector collet to provide strain relief  
-Insulate all LEMO solder joints with item 4



WIRE ENTRY  
FGG.0B.305.CLAD52Z

BILL OF MATERIALS

Item	Qty	Manufacturer	Manufacturer PN	Description	Racelogic PN
1	1	LEMO	FGG.0B.304.CLAD52Z	LEMO 4W Cable Plug	LEMO 4WAY P
2	2m	MULTICOMP	MP002328	7-2-04A 4-Core Unscreened Cable	119-0211
3	1	Avery	J8658-26	Cable Ident 25.4mm x 10mm	
4	A/R	PRO-POWER	SP3X15/5/BLACK	Heatshrink Black 1.5mm 3:1	119-1021
5	30mm	PRO-POWER	CGFC-6/2C	Heatshrink Clear 6mm 3:1	304-6539
6	1	LEMO	FGG.0B.305.CLAD52Z	LEMO 5W Cable Plug	LEMO 5WAY P
7	2	LEMO	GMA.0B.035.DN	LEMO Black Strain Boot	GMA.0B.035.D
8	A/R	PRO-POWER	13636	Heatshrink Black 4.8mm 2:1	100-8431

Connection Table

4W LEMO			5W LEMO
Pin	Function	Colour	Pin
3	CAN H	Green	3
4	CAN L	Yellow	4
1	POWER	Red	5
2	GND	Blue	Shell

DRAWING NUMBER	RLCAB184	DRAWN	S.HOOPER	SHEET	1/1
DESCRIPTION	STEERING SENSOR CAN+PWR CABLE				
REVISION					
ISS	DESCRIPTION	DATE	APPROVED	REDMINE	
1	FIRST ISSUE	24-06-21	BS	17212	